

## **TED TODD**

## SPECIFICATION SHEET

## RYHILL WIDE PLANK

Item code: PROJ029

Collection: Project

Overview		
Wood Species	European Oak	
Design	Plank	
Grade	Nature	
Profile	Tongue & grooved to all sides	
Edge Detail	Micro bevelled	
Construction	3 Layer Engineered	
Wear Layer	3mm Hardwood (Nominal)	
Application Guide	Floors, walls & ceilings	
Dimensions		
Width	190mm	
Thickness	14mm	
Length	Up to 1.90m (Random)	
Tolerance	+/- 0.50mm / 95% in tolerance	
Pack Size, M2	2.888 m2 - order to the nearest pack size	
Finish		
Finish	Hardened Oil	
Surface Texture	Medium brushed	
Tonal Variation	Medium natural tonal variation	
Batch Variation	Not advised to mix batches in one floor area	
Handover guidance	Fully finished, ready for use.	
Floor Care	Care System 1	
Environmental Certification		
Certification	FSC 100% - independently audited, since 1997, chain of custody tracking	
UKTR Compliant	Yes	
Installation Guidelines		
Floating Installation	Yes - Ted Todd - range of underlays	
Secret Nail	Not recommended	
Structural Floor	No	



Fully Bond	Yes - Ted Todd MS Flex high strength adhesive
Sub floor Primer	Yes - Ted Todd Primerfast
Underfloor Heating	Yes - please see usage guidelines
Sub Floors	
Concrete	Dry, Flat
Plywood	Yes
Screed	Dry, flat, with Primerfast moisture barrier
Formed Tread + Riser	Yes - Made to order - 14 day service
L Section, T Section, Reducer, Scotia	Yes - 7 day service
Skirting, Architrave	Yes by request
Technical Information	
Moisture Content	8-12% fair and average moisure content
Slip Rating	Low risk dry. Low risk wet.
EN 13501-1 Fire Rating Flooring	Efl
EN 14342 Emissions	E1
Humidity requirements	Between 40 and 60% relative humidity
Origin	European
Janka Hardness Rating	1,120 lbf (4980N)
Formaldehyde Emission	E1
Thermal Conductivity	15mm 0.08m2K/W, 0.8 Tog
Shipping Information	1
Shipment times	Largest UK Stocks - available 3 day service
Packaging	Palletised, wrapped + banded
Guarantee	
Warranty	30 year product warranty
Life Cycle	
Life Span	Generational life span if cared for
Recycle	Value in recycling into upscale uses, worst case outcome carbon neutral
Reuse	Reclaim and re-use as flooring









