

Xpressions 8/32 Laminate Flooring

megaloc



Anti Bacterial




Realistic decor



PVC free



Extremely resistant



4V groove

Carbon-negative production based on highly efficient industrial processes



Exclusive product-design consistently oriented towards recycling



Fully integrated production-process on 1 site






Choose from exclusive designs and colours

Standards		Xpressions 8/32
CLASSIFICATION		
Product Performance	EN 13329	AC-4
European Classification	DIN EN 13329	32
PERFORMANCE		
Fire Reaction	EN 13501-1	Cfl-s1
Abrasion Resistance	EN 13329	≥ 4000 cycles
Impact Resistance	EN 17368 EN 13329	≥ 750 mm
Residual Indentation	EN ISO 24343-1	≤ 0.05 mm
Castor Chair Resistance	EN 425	no damage with type W after 25 000 cycles
Furniture Leg Resistance	EN ISO 16581	no damage with type 0
Slip Resistance	EN 13893	DS
Stain Resistance	EN 438-2	Class 5 (group 1 and 2), Class 4 (group 3)
Thermal Conductivity	EN 12667	≥ 0.075 W/mK
Thermal Resistance	EN 12667	R ≤ 0.06 (m²K)/W
Electrostatic Behaviour	EN 1815	≤ 2 kV
ENVIRONMENT		
VOC Emissions	ISO 160001-6	<100 / A+
Formaldehyde	ISO 16516	E1
DESCRIPTION		
Product Description	Laminate flooring with Megaloc Click-System	
Usage Type	Class 32: domestic and moderate commercial use	
Guarantee	10 years for heavy domestic use, 5 years for moderate commercial use	
CONDITIONING		
Xpressions 8/32 box of 9 planks of 1286 x 194 x 8mm - 2.245m² per box (44 boxes per pallet)		
IMPLEMENTATION - MAINTENANCE TIPS		
WWW.LIBERTY-FLOOR.COM		

Patented Click System

megaloc



- ① 4 Sided Bevel
- ② Overlapping Bevels
- ③ Durable Force Locking Connection



Installation Demo